



20 608 SD0 ALLURE BRILLIANT ICON 3D 3-HOLE WALL-MOUNT BASIN MIXER



PRODUCT DESCRIPTION

- Colour: stainless steel
- GROHE Water Saving 5.0 l/min. flow limiter
- spout with integrated mousseur
- red and blue markings on handles for hot and cold water
- valves hot/cold with ceramic headparts
- pressure-proof, flexible connection hoses between spout and side valves
- projection 256 mm
- technical data
- flow pressure min 0.5 bar
- recommended pressure 1.0 - 5.0 bar
- if static pressure is more than 5 bar fit pressure reducer
- avoid major pressure differences between cold and hot water supply
- flow rate at 3 bar flow pressure: approx. 5 l/min
- max. temperature hot water inlet: 80°C
- recommended temperature hot water inlet (energy saving): 60°C

20 608 SD0 ALLURE BRILLIANT ICON 3D 3-HOLE WALL-MOUNT BASIN MIXER



SELECT SPARE PART: , September 2018 – spareParts.validDate.now

1: Ceramic headpart, 1/2" (Order-nr. 45882000)

1.1: O-ring $\varnothing 18.2 \times \varnothing 1.7$ (Order-nr. 0392400M)

2: Ceramic headpart, 1/2" (Order-nr. 45883000)

2.1: O-ring $\varnothing 18.2 \times \varnothing 1.7$ (Order-nr. 0392400M)

3: Flexible connection hose (Order-nr. 45704000)

4: Coupling nut 1/2" x 10.5 mm (Order-nr. 1290100M)

4.1: Fibre seal dia. 12x2 mm (Order-nr. 0138900M)

5: Waste set with push-open plug (Order-nr. 65807000)

6: Coupling nut 1/2" x 14.5 mm (Order-nr. 1290200M)*

* Optional accessories